


Product card



PARAFFIN

Brief product information

High-quality paraffins, odorless, with stable color and low sulfur content, obtained as a result of hydrotreatment process. The product fulfills the requirements of RAL-GZ 041 standard.

Application

The product intended for the production of candles and in the paper, food, and chemical industry.

OPD guaranteed quality parameters

- Sulfur content, max. 20 [ppm]
- Oil content, max. 0.75 wt%
- Saybolt color: min. +24
- Penetration: max. 20 x 0.1 mm
- Solidification point: 54-58°C
- Ash content: max. 0.05%
- Odor: max. 2
- RAL test for UV color stability: min. +15
- Kinematic viscosity at 100°C: mark
- PAH content test: endures
- Benzene content: max 0.5 [ppm]
- Toluene content: max. 5.0 [ppm]

Storage

Packaging should be stored in closed rooms protecting against humidity, mechanical contaminants, direct impact of sunlight and heating devices.

Transport and sales

Transport: Paraffin is not subject to RID and ADR regulations regarding the carriage dangerous of goods. It can be transported by any means of transport.

Sales: in tank trucks or packed: granulated product (20 kg bags)

DYSTRYBUTOR

Ecoflores

ul. Waksmundzka 34

34-400 Nowy Targ, Polska

WWW.ECOFLORES.EU

tel: +48 604-508-229

kontakt@ecoflores.eu